20t TELESCOPIC SPREADER BEAM



MODEL TSB1206

SPECIFICATION

Tare Weight: 0.215t (Excl. slings/shackles)

Lifting lugs (top) suit: 17t Grade S bow shackle

Load lugs (lower) suit: 12t Grade S bow shackle

Centre lug suits: 4.7t Grade S bow shackle

ASSURANCE

Compliance Standard: AS4991-2004

Proof load tested: Yes

NDT Weld Inspection: Yes

Standard Finish*: Painted (G36 Green)

ð

*Other colours/finishes available on request

Span	WLL (at included sling angle)				Approx. Sling Leg Length (Mtrs)			Approx. Headroom (Mtrs)		
(Mtrs)	60°	90°	120°	CENTRE LIFT	60°	90°	120°	60°	90°	120°
4.0m	20t	14t	8t	2.1t	4.0	2.8	2.3	3.5	2.0	1.2
4.5m	20t	14t	8t	1.9t	4.5	3.2	2.6	3.9	2.3	1.3
5.0m	20t	14t	8t	1.7t	5.0	3.5	2.9	4.3	2.5	1.4
5.5m	20t	14t	8t	1.5t	5.5	3.9	3.2	4.8	2.8	1.6
6.0m	20t	14t	8t	1.3t	6.0	4.2	3.5	5.2	3.0	1.7





